


U.I. Lapp GmbH	PRODUCT INFORMATION	
	SILVYN® SSUE	12.09.2012

High-tensile
Corrosion-resistant
Flexible
For high mechanical stress
Heat-resistant



Application range

Offshore applications
Measuring technology
Plant engineering
Outdoors
Applications with high mechanical stress

Design

Spirally-wound stainless steel protective conduit with roughened profile

Approvals (Norm references)

UNDERGROUND

Note

Sizes 10, 12 with double-interlocked Agraff profile

Product features

Stainless steel AISI 316

Remark

Photographs are not to scale and do not represent detailed images of the respective products.


Technical Data


Approvals (Norm references):	Railway: UNDERGROUND, Link-up
Note:	Sizes 10, 12 with double-interlocked Agraff profile
Material:	Stainless steel AISI 316
Protection rating:	IP 40
Temperature range:	-100°C to +400°C

Product Management	Document: LAPP_PRO1209EN.pdf	1 / 3
--------------------	------------------------------	-------




Part number	Article designation	Internal Ø x external Ø (mm)	Bending radius (mm)	Inner Ø (mm)	Suitable for SILVYN® LGEF-M/LGES-M	PU ring (m)
SILVYN® SSUE						
61804600	10	6,8 x 9	25	6.8	M 12 x 1,5	25.0
61804601	12	10,2 x 13	30	10.2	M 16 x 1,5/1	25.0
61804602	16	13 x 16	40	13	M 16 x 1,5/2	25.0
61804603	20	16,9 x 20,5	45	16.9	M 20 x 1,5/1	25.0
61804604	25	21,1 x 25	55	21.1	M 25 x 1,5	25.0
61804605	32	28,1 x 32	70	28.1	M 32 x 1,5	25.0
61804612	40	37,6 x 42,5	80	37.6	M 40 x 1,5	10.0
61804613	50	48,4 x 53	90	48.4	M 50 x 1,5	10.0

U.I. Lapp GmbH	PRODUCT INFORMATION	 LAPP GROUP
	SILVYN® SSUE	12.09.2012



SILVYN® LGEF-M



SILVYN® LGES-M