


U.I. Lapp GmbH	PRODUCT INFORMATION	
	SILVYN® OR	12.09.2012

Protects against liquids
 High-tensile
 Robust
 High crush-resistance
 Highly oil and acid-resistant



Application range

Mechanical engineering
 Plant engineering
 Transformer construction
 Railway applications
 Paper industry

Design

Spirally-wound heavy metal protective conduit with roughened profile
 Plastic outer sheath

Note

PU = 10 m (on request)

Remark

Photographs are not to scale and do not represent detailed images of the respective products.

Technical Data

Colour delivered:	Black
Material:	Galvanized steel with special PVC sheath
Temperature range:	-20°C to +100°C Short-term: up to +120°C


Product Management	Document: LAPP_PRO1218EN.pdf	1 / 3
--------------------	------------------------------	-------



SILVYN® OR

12.09.2012

Part number	Article designation	Internal Ø x external Ø (mm)	Bending radius (mm)	Inner Ø (mm)
SILVYN® OR				
61712840	3/8"	12,6 x 17,8	85	12.6
61712850	1/2"	16 x 21,1	110	16
61712860	3/4"	21 x 26,4	140	21
61712870	1."	26,5 x 33	170	26.5
61712880	1 1/4"	35,1 x 41,8	215	35.1
61712890	1 1/2"	40,3 x 47,8	250	40.3
61712900	2."	51,6 x 59,9	300	51.6

U.I. Lapp GmbH	PRODUCT INFORMATION	
	SILVYN® OR	12.09.2012



SILVYN® ADG/ADG-M
IP 67



SILVYN® ADHW/ADHW-M
IP 67



SILVYN® ADW/ADW-M
IP 67



SILVYN® FDG
IP 66



SILVYN® FDHW
IP 66



SILVYN® FDW
IP 66



SILVYN® TB-E

Product Management	Document: LAPP_PRO1218EN.pdf	3 / 3
--------------------	------------------------------	-------