


U.I. Lapp GmbH	PRODUCT INFORMATION	
	SILVYN® LCCH-2	12.09.2012

High flame-retardance and self-extinguishing in accordance with UL 94V-0
 Protects against liquids
 High crush-resistance
 Suitable for outdoor use and direct burial
 High mechanical resistance



Application range

Public utilities
 Mechanical engineering
 Outdoors
 Used in areas where liquids are present
 Applications with high mechanical stress

Design

Spirally-wound metal protective conduit with roughened profile
 Plastic outer sheath

Approvals (Norm references)

UNDERGROUND
 LLOYD'S REGISTER

Product features

Halogen-free
 Less fumes
 Low toxicity

Remark

Photographs are not to scale and do not represent detailed images of the respective products.

Technical Data

Colour delivered:	Black (RAL 9005)
Material:	Inner conduit: steel, galvanised Outer sheath: plastic, halogen-free
Temperature range:	-25°C to +90°C


Product Management	Document: LAPP_PRO1202EN.pdf	1 / 3
--------------------	------------------------------	-------




SILVYN® LCCH-2


12.09.2012

Part number	Article designation	Internal Ø x external Ø (mm)	Bending radius (mm)	Inner Ø (mm)	PU ring (m)
SILVYN® LCCH-2					
61804793	LCCH-2 / 12	10,2 x 14	30	10.2	25.0
61804794	LCCH-2 / 16	13 x 17	40	13	25.0
61804795	LCCH-2 / 20	16,9 x 21,5	45	16.9	25.0
61804796	LCCH-2 / 25	21,1 x 26	55	21.1	25.0
61804797	LCCH-2 / 32	28,1 x 34	70	28.1	25.0
61804798	LCCH-2 / 40	37,6 x 44,5	80	37.6	10.0
61804799	LCCH-2 / 50	48,4 x 55	90	48.4	10.0


U.I. Lapp GmbH	PRODUCT INFORMATION	
	SILVYN® LCCH-2	12.09.2012




SILVYN® LGF-2-M




SILVYN®
LGS-2-M/LGS-2



SILVYN® LCG-M



SILVYN® LCW-M



SILVYN® SAT

Product Management	Document: LAPP_PRO1202EN.pdf	3 / 3
--------------------	------------------------------	-------