

U.I. Lapp GmbH	PRODUCT INFORMATION	
	SILVYN® MAXI PA	12.09.2012

Dimensionally stable
Flexible
High flame-retardance and self-extinguishing in accordance with UL 94V-0
Crush-resistant



Application range

Mechanical engineering
Public utilities
Moving applications
Outdoors

Design

Thick-walled corrugated polyamide 6 conduit

Approvals (Norm references)

UL FILENUMBER E308201

Note

UV-resistant and weather-resistant

Product features

Halogen and cadmium-free
Abrasion-resistant
High resistance to oil, petrol, acids and other chemicals

Remark

Photographs are not to scale and do not represent detailed images of the respective products.

Technical Data

On request:	Available in PA 12
Colour delivered:	Grey (RAL 7001) Black (RAL 9005), UV-resistant
Material:	PA 6 Halogen-free
Temperature range:	-40°C to +115°C short-term +150°C

Product Management	Document: LAPP_PRO1188EN.pdf	1 / 2
--------------------	------------------------------	-------



SILVYN® MAXI PA

12.09.2012

Part number	Internal Ø x external Ø (mm)	Bending radius (mm)	Inner Ø (mm)	Weight (kg/m)	Suitable for SILVYN® AFG-PA/AFW-PA	PU ring (m)
SILVYN® MAXI PA grey						
61791150	66,5 x 79,2	170	66.5	0.46	70	10.0
61791160	91 x 106	225	91	0.79	95	10.0
SILVYN® MAXI PA black						
61791155	66,5 x 79,2	170	66.5	0.46	70	10.0
61791165	91 x 106	225	91	0.79	95	10.0