

U.I. Lapp GmbH	<b>PRODUCT INFORMATION</b>	
	<b>SILVYN® SI</b>	<b>12.09.2012</b>

Protection against dust  
Protection against humidity  
Low abrasion protection



### Application range

Easy cable protection  
Additional insulation  
Bundling and guiding of cables and wires

### Design

Soft-PVC conduit

### Product features

Flexible  
Soft

### Remark

Photographs are not to scale and do not represent detailed images of the respective products.

### Technical Data

Note:

Flame-retardant and self-extinguishing  
Dielectric strength: 25 kV/mm  
Tear-resistance: 23 N/mm<sup>2</sup>  
Shore A hardness: 75 °C to 90 °C

Colour delivered:

Silver grey (RAL 7001)

Material:

Soft PVC

Temperature range:

-5 °C to +80 °C

Product Management	Document: LAPP_PRO1125EN.pdf	1 / 3
--------------------	------------------------------	-------




SILVYN® SI


12.09.2012

Part number	Internal Ø x external Ø (mm)	Inner Ø (mm)	Suitable for SILVYN® SSV-M/SSVZ-M	Suitable for SILVYN® SSV/SSVZ	Suitable for SILVYN® SCH
SILVYN® SI					
61713210	7 x 9	7	12.1/-		10 - 16 S
61713240	9 x 12	9	12.2/-		
61713270	11 x 14	11	16.1 / -		10 - 16 S
61713300	13 x 16	13	16.2 / -		12 - 20 S
61713330	14 x 18	14	20.1 / 20/11/14		12 - 20 S
61713360	18 x 22	18	20.3 / 20/13/18	13,5.1	16 - 25 S
61713390	23 x 28	23	25 / 25/21/24	21,1	25 - 40 S
61713420	32 x 38	32	32 / 32/29/32	29,2	32 - 50 S


U.I. Lapp GmbH	<b>PRODUCT INFORMATION</b>	
	<b>SILVYN® SI</b>	<b>12.09.2012</b>



SILVYN® SSV/SSV-M + SCH  
IP 54



SILVYN®  
SSVZ/SSVZ-M + SCH  
IP 54



SILVYN®  
USK/USK-M  
IP 65



SILVYN® SCH

Product Management	Document: LAPP_PRO1125EN.pdf	3 / 3
--------------------	------------------------------	-------