

U.I. Lapp GmbH	PRODUCT INFORMATION	
	HITRONIC® HQW Armoured Outdoor Cable	12.09.2012

Armouring provides excellent protection against high mechanical stress and rodents
Suitable for direct burial
Easy to install due to the compact design, high flexibility, robust sheath and small bending radii
UV and water-resistant



Info

A-DQ(ZN)(SR)2Y

Outdoor cable with corrugated steel tape armour, central loose tube and non-metallic strain relief

Application range

For outdoor use
Campus backbone
WAN applications
Industrial environments
Methods of Deployment: empty plastic pipes, ducts and trays

Design

Gel-filled loose tube
Water-blocking reinforced glass yarn strain relief
Corrugated steel tape armour
PE outer sheath
Colour: black (RAL 9005)

Product features

Central loose tube with up to 24 fibres
Colour-coded fibres
Longitudinal watertight
Excellent rodent protection
Robust, halogen-free outer sheath

Remark

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

The cables can also be supplied as pre-terminated fibre optic trunks.

Photographs are not to scale and do not represent detailed images of the respective products.

Technical Data

Optical fibre type:	Core material: glass Cladding material: glass
Temperature range:	Fixed installation: -50°C to +100°C Occasional flexing: -30°C to +70°C
Permissible bending radius:	Static: ≥ 15 x outer diameter Dynamic: ≥ 20 x outer diameter
Permissible tensile force:	Long-term: 3000 N Short-term: 5000 N

Product Management	Document: LAPP_PRO205974EN.pdf	1 / 2
--------------------	--------------------------------	-------

**HITRONIC® HQW Armoured Outdoor Cable**

12.09.2012

Part number	Article designation	Fibre type	Number of fibres	Outer diameter (mm)	Weight (kg/km)
Multimode G 50 OM3					
27900304	HITRONIC® HQW3000 4G 50/125 OM3	50/125 OM3	4	9.6	88
27900308	HITRONIC® HQW3000 8G 50/125 OM3	50/125 OM3	8	9.6	88
27900312	HITRONIC® HQW3000 12G 50/125 OM3	50/125 OM3	12	9.6	88
27900324	HITRONIC® HQW3000 24G 50/125 OM3	50/125 OM3	24	9.6	88
Multimode G 50 OM2					
27900204	HITRONIC® HQW3000 4G 50/125 OM2	50/125 OM2	4	9.6	88
27900208	HITRONIC® HQW3000 8G 50/125 OM2	50/125 OM2	8	9.6	88
27900212	HITRONIC® HQW3000 12G 50/125 OM2	50/125 OM2	12	9.6	88
27900224	HITRONIC® HQW3000 24G 50/125 OM2	50/125 OM2	24	9.6	88
Multimode G 62.5 OM1					
27900104	HITRONIC® HQW3000 4G 62.5/125 OM1	62.5/125 OM1	4	9.6	88
27900108	HITRONIC® HQW3000 8G 62.5/125 OM1	62.5/125 OM1	8	9.6	88
27900112	HITRONIC® HQW3000 12G 62.5/125 OM1	62.5/125 OM1	12	9.6	88
27900124	HITRONIC® HQW3000 24G 62.5/125 OM1	62.5/125 OM1	24	9.6	88
Single-mode E 9 OS2					
27900904	HITRONIC® HQW3000 4E 9/125 OS2	9/125 OS2	4	9.6	88
27900908	HITRONIC® HQW3000 8E 9/125 OS2	9/125 OS2	8	9.6	88
27900912	HITRONIC® HQW3000 12E 9/125 OS2	9/125 OS2	12	9.6	88
27900924	HITRONIC® HQW3000 24E 9/125 OS2	9/125 OS2	24	9.6	88