


## Multi-Lok Ties

- Self Locking
- Flame retardant
- U.V. and corrosion resistant
- Applied by hand or M503, KE922, AE200 and AE201 tools
- Tensile Strength > 90 Kg.
- Coated in Nylon 11 For greater corrosion resistance
- Excellent minimum loop tensile strength. In excess of 890N (7mm wide) and 1112N (12mm wide) for both coated and uncoated versions



### Multi-Lok Ties Coated

Pkg. Qty 100



Type 316 Stainless Steel Coated with Nylon 11

| Cat. No. | Maximum Bundle Dia |     | Width |    | Length |     | Weight |      |
|----------|--------------------|-----|-------|----|--------|-----|--------|------|
|          | In.                | mm  | In.   | mm | In.    | mm  | Lbs.   | Kg.  |
| AE611    | 1.3                | 33  | 0.28  | 7  | 6      | 150 | 0.66   | 0.30 |
| AE612    | 2.2                | 57  | 0.28  | 7  | 9      | 225 | 0.99   | 0.45 |
| AE613    | 3.2                | 81  | 0.28  | 7  | 12     | 300 | 1.32   | 0.60 |
| AE614    | 5.1                | 129 | 0.28  | 7  | 18     | 450 | 1.76   | 0.80 |
| AE615    | 7.1                | 180 | 0.28  | 7  | 24     | 610 | 2.64   | 1.20 |
| AE711    | 1.3                | 33  | 0.47  | 12 | 6      | 150 | 1.10   | 0.50 |
| AE712    | 2.2                | 57  | 0.47  | 12 | 9      | 225 | 1.65   | 0.75 |
| AE713    | 3.2                | 81  | 0.47  | 12 | 12     | 300 | 2.20   | 1.00 |
| AE714    | 5.1                | 129 | 0.47  | 12 | 18     | 450 | 2.97   | 1.35 |
| AE715    | 7.1                | 180 | 0.47  | 12 | 24     | 610 | 4.29   | 1.95 |



### Multi-Lok Ties Uncoated

Pkg. Qty 100



Type 316 Stainless Steel Uncoated

| Cat. No. | Maximum Bundle Dia |     | Width |    | Length |     | Weight |      |
|----------|--------------------|-----|-------|----|--------|-----|--------|------|
|          | In.                | mm  | In.   | mm | In.    | mm  | Lbs.   | Kg.  |
| AE601    | 1.3                | 33  | 0.28  | 7  | 6      | 150 | 0.66   | 0.30 |
| AE602    | 2.2                | 57  | 0.28  | 7  | 9      | 225 | 0.81   | 0.40 |
| AE603    | 3.2                | 81  | 0.28  | 7  | 12     | 300 | 1.21   | 0.55 |
| AE604    | 5.1                | 129 | 0.28  | 7  | 18     | 450 | 1.98   | 0.90 |
| AE605    | 7.1                | 180 | 0.28  | 7  | 24     | 610 | 2.64   | 1.20 |
| AE701    | 1.3                | 33  | 0.47  | 12 | 6      | 150 | 1.10   | 0.50 |
| AE702    | 2.2                | 57  | 0.47  | 12 | 9      | 225 | 1.65   | 0.75 |
| AE703    | 3.2                | 81  | 0.47  | 12 | 12     | 300 | 2.20   | 1.00 |
| AE704    | 5.1                | 129 | 0.47  | 12 | 18     | 450 | 3.19   | 1.45 |
| AE705    | 7.1                | 180 | 0.47  | 12 | 24     | 610 | 4.29   | 1.95 |

## Application Tools



M503 Multi-Lok tool with adjustable tension and automatic cut off weight 0.94Lbs. (.43Kg.)



KE922 Manual Tensioning tool with cut off lever Weight 1.25Lbs. (.57Kg.)



AE200 Tensioner See page 14 for details



AE201 Tensioning Hook See page 14 for details